

Pre-coated chippings

Technical data sheet

Heidelberg Materials' pre-coated chippings product range includes Clause 943 hot rolled asphalt (HRA) surface course and binder course (performance-related design mixtures).

HRA is a dense, gap graded asphalt designed to be used in a wide range of applications. Pre-coated chippings are highly resistant to polishing and are rolled into, and form part of, an HRA surface course. Heidelberg Materials' offers a range of pre-coated chippings with varying polished stone values (PSV) which vary according to the asphalt plant they are produced at:

- Craig Yr Hesg – 68+ PSV
- Runcorn – 60, 65, 68 PSV
- Bradford – 60 PSV
- Keepersfield – 55, 60, 65, 68 PSV
- Criggion 60, 68 PSV

Benefits

- Use of high quality aggregates in accordance with BS EN 13043
- Availability of coated chippings for surface course when required
- SHW, EN and PD compliant
- Available in bulk and as a packed product.
See: heidelberg-packedproducts.co.uk

Please note: we are able to deliver on a nationwide basis.

Please see asphalt product matrix for further information or contact technical:

northasphaltsales@uk.heidelbergmaterials.com
southwestasphaltsales@uk.heidelbergmaterials.com
southwalesasphaltsales@uk.heidelbergmaterials.com
southeastasphaltsales@uk.heidelbergmaterials.com



**SKID
RESISTANCE**